




全国统一服务热线: 400-1166-021

首页 | 关于公司 | 条码产品 | 自主开发 | 应用方案 | 下载中心 | 条码知识 | 条码新闻 | 在线留言 | 联系我们

- 条码打印机
- 条码扫描器
- 数据采集器
- 条形码软件



关闭 条码标签机 > 美国zebra标签打印机 > Zebra TTP 2110条码打印机



**Zebra TTP 2110 Thermal Receipt Printers**

The TTP 2110 direct thermal printer is small enough to fit in the palm of your hand, yet robust enough for use in most ticketing applications, such as ATBI boarding passes, bag tags, and tickets. By replacing traditional magnetic stripe technology with a simple linear or 2-D bar code, the TTP 2110 eliminates the costliest component in a ticketing system and offers a more economical alternative to traditional solutions. The automatic media detector makes it possible to load boarding passes or bag tags without adjustment. The ticket format is variable up to 82.5 mm/3.25" wide and 600 mm/23.6" long - so the TTP 2110 is ideal for printing ATBI boarding passes, and IATA CUSS bag tags (with lengths up to 533 mm/21"). The TTP 2110 series' compact size makes the desktop version an attractive choice for both attended and unattended ticketing applications, while the embedded version fits neatly in kiosk designs.

**Standard Features**

- RS-232 Serial Interface
- Compact size 2-D bar coding

Media sensors - out-of-paper, paper in Presenter, top of form selectable for for or reflective settings, input for external paper-low sensor  
Prints ATBI boarding passes, bag tags, and tickets

**Printer Specifications**

- Resolution 203 dpi (8 dots/mm)
- Print width 2.13" (54 mm) for credit card size 3.15" (80 mm) for ATBI size media
- Print length 23.6" (600 mm)
- Print speed 5.9" (150 mm)/sec

**Media Characteristics**

- Maximum roll diameter 9.8" (250 mm)
- Media thickness 0.004" (0.11 mm) to 0.01" (0.26 mm) for 2.13" (54 mm) paper
- Media types
- Roll or fanfold

**Operating Characteristics**

- Operating temperature
- DT: Operating temperature 32° F (0° C) to 122° F (50° C) Direct thermal
- Storage temperatures 14° F (-10° C) to 122° F (50° C)
- Operating humidity 35-75% non-condensing R.H.
- Storage humidity 10-90% non-condensing excluding paper
- Electrical 24Vdc +/- 5% average 2A, peak 6A

**Physical Characteristics**

- Width Embedded: 4.1" (105 mm) - Desktop: 4.5" (115 mm)
- Height Embedded: 2.6" - Desktop: 3.1" (Embedded: 65 mm - Desktop: 80 mm)
- Depth Embedded: 5.7" - Desktop: 7.1" (Embedded: 145 mm - Desktop: 180 mm)
- Weight Embedded: 2.4 lbs - Desktop: 3.1 lbs (Embedded: 1.1 kg - Desktop: 1.4 kg)

**Related Products**

- Options
- Print guides for 51, 54, 60, 66, 80 and 82.5 mm media
- Leaf spring retainer for quick fit hubs
- Media holder (includes quick fit hubs and spring)
- Paper-low sensor with 300 mm cable
- Output tray
- Communication and Interface Capabilities
- Serial RS232



**条码打印机**

- 美国Intermec条码打印机
- 日本Tec条码打印机
- 美国Zebra条码打印机
- 日本Sato条码打印机
- 日本Ring条码打印机
- 美国Datamax条码打印机
- 美国Printronic条码打印机
- 台湾Godex条码打印机
- 日本Toshiba条码打印机
- 日本Shinsei条码打印机
- 日本Citizen条码打印机
- 台湾TSC条码打印机
- 韩国Woosim条码打印机
- 德国CAB条码打印机

**条码扫描器**

**数据采集器**

**无线局域网**

**条码标签**

**条码碳带**

**条码软件**

**条码检测仪**

**条码打印机配件**

**Rfid电子标签**

销售热线

021-51088173  
021-51088351

热销产品



Windows 2000, XP, Server 2003, OPOS  
Bar Codes/Symbologies  
Linear  
EAN-8  
EAN-13  
UCC/EAN-128  
UPC  
Interleaved 2-of-5  
ISBN  
Code 39  
Code 128  
2-D PDF 417  
Fonts and Graphics  
Any font or graphic supported by the operating system

[条码新闻](#) | [网站地图](#) | [友情链接](#) | [人才招聘](#) | [法律条款](#) | [在线解答](#) | [联系我们](#)  
版权所有 © 2005-2011 上海竞阳科技  
电话: 021-51088351 51088173 传真: 021-58527920  
地址: 上海市浦东大道1097号15号楼3层D座 邮编: 200135 邮箱: mail@gyoung.com.cn