



全国统一服务热线: 400-1166-021

首页 | 关于公司 | 条码产品 | 自主开发 | 应用方案 | 下载中心 | 条码知识 | 条码新闻 | 在线留言 | 联系我们

条码打印机
条码扫描器
数据采集器
条形码软件

竞阳科技 条码专家



条码打印机

- 美国Intermec条码打印机
- 日本Tec条码打印机
- 美国Zebra条码打印机
- 日本Sato条码打印机
- 日本Ring条码打印机
- 美国Datamax条码打印机
- 美国Printronic条码打印机
- 台湾Godex条码打印机
- 日本Toshiba条码打印机
- 日本Shinsei条码打印机
- 日本Citizen条码打印机
- 台湾TSC条码打印机
- 韩国Woosim条码打印机
- 德国CAB条码打印机

条码扫描器

数据采集器

无线局域网

条码标签

条码碳带

条码软件

条码检测仪

条码打印机配件

Rfid电子标签

条码标签机 > 美国Zebra标签打印机 > Zebra TTP 7030条码打印机



Zebra TTP 7030 Thermal Receipt Printers

The TTP 7030 is a fast, reliable, and versatile kiosk printer specially designed for unattended operation. It's built to work in harsh environments such as heat, cold, and vibration. And with the jam-preventing loop presenter, guillotine cutter, and pull detector, the TTP 7030 provides trouble-free operation. The only maintenance required is to replace the media roll. The TTP 7030 can support 80/3.5" to 112 mm/4.4" media width, plus a wide printing format that provides room for extensive information or graphics, allowing Web- or A4-pages to be downscaled into pocket format. When connected via USB interface, the printer is plug-and-play compatible with Windows or the printer can be addressed directly from the kiosk software in text mode. The TTP 7030 has Flash memory to store large downloaded files like fonts and graphics.

Standard Features

USB interface

Printer Specifications

Resolution 203 dpi (8 dots/mm)

Print width TTP7030/80: 2.83" (72 mm)

TTP7030/112: 4.09" (104 mm)

Print length 2.95" (75 mm) to 24" (600 mm)

Print speed 2.95" (75 mm)/sec

Media Characteristics

Media thickness .002" (.054mm) to .005" (.13 mm)

Media types

continuous

Operating Characteristics

Storage temperatures ° F to ° F

Operating humidity 23° F (-5° C) to 104° F (40° C)

Electrical TTP 7030/80: 24 VDC, ± 10%, average 2.5 A, peak 8.5 A

TTP 7030/112: 24 VDC, ± 10%, average 3.5 A, peak 11 A

Agency approvals UL CE Physical Characteristics

Width 80: 5.35" (136 mm)

Height 5.39" (137 mm)

Depth 5.9" (150 mm)

Weight 5.51 lbs (2.5 kg)

Related Products

Options

Retract sensor

weekend paper low sensor

RS-232 Serial interface

Communication and Interface Capabilities

USB

Optional Serial RS-232

Windows and Linux drivers. Direct addressing with ESC sequences.

Bar Codes/Symbologies

Linear

Code 39

Code 128

EAN-8 and EAN-13 with 2 or 5 digit extensions

Interleaved 2-of-5

Fonts and Graphics

销售热线

021-51088173

021-51088351

热销产品



Up to eight fonts of 256 characters, Fixed or proportional

[条码新闻](#) | [网站地图](#) | [友情链接](#) | [人才招聘](#) | [法律条款](#) | [在线解答](#) | [联系我们](#)

版权所有 © 2005-2011 上海竞阳科技

电话: 021-51088351 51088173 传真: 021-58527920

地址: 上海市浦东大道1097号15号楼3层D座 邮编: 200135 邮箱: mail@gyoung.com.cn