



全国统一服务热线: 400-1166-021

首页 | 关于公司 | 条码产品 | 自主开发 | 应用方案 | 下载中心 | 条码知识 | 条码新闻 | 在线留言 | 联系我们

条码打印机
条码扫描器
数据采集器
条形码软件

竞阳科技 条码专家



条码打印机

- 美国Intermec条码打印机
- 日本Tec条码打印机
- 美国Zebra条码打印机
- 日本Sato条码打印机
- 日本Ring条码打印机
- 美国Datamax条码打印机
- 美国Printronix条码打印机
- 台湾Godex条码打印机
- 日本Toshiba条码打印机
- 日本Shinsei条码打印机
- 日本Citizen条码打印机
- 台湾TSC条码打印机
- 韩国Woosim条码打印机
- 德国CAB条码打印机

条码扫描器

数据采集器

无线局域网

条码标签

条码碳带

条码软件

条码检测仪

条码打印机配件

Rfid电子标签

条码标签机 > 美国Zebra标签打印机 > Zebra TTP 8300条码打印机



Zebra TTP 8300 Thermal Receipt Printers

The TTP 8300 series kiosk printers offer 300-dpi resolution for extremely sharp, full-format A4 or letter-size printouts of forms, bank statements, maps, or Web pages. The fast, compact, and low-maintenance design makes the printer ideal for unattended environments. The pull detector and jam-preventing loop presenter provide trouble-free operation. The retract function keeps sensitive documents from being left behind outside the kiosk—and it saves media. If a printout is not taken from the printer, the output will be retracted and the remaining information can be deleted from the print queue, eliminating unwanted print jobs. The TTP 8300 is available in three configurations for flexible kiosk integration: standard, compact, and vertical, each equipped with standard USB and parallel interfaces. For additional configuration flexibility, the media can be mounted either behind or below the printer.

Standard Features

- USB and IEEE-1284 interfaces
- Printer Specifications
- Resolution 300 dpi (12 dots/mm)
- Print width 8.5" (216 mm)
- Print length Letter: 11" (279 mm) A4: 11.7" (297 mm)
- Print speed 2.60" (66 mm)/sec
- Media Characteristics
- Maximum roll diameter 9.84 (250 mm)
- Core diameter 1" (25 mm)
- Media thickness .002" (.054 mm) to .004" (.1 mm)
- Media types continuous, fanfold

Operating Characteristics

- Operating temperature DT: Operating temperature 32° F (0° C) to 122° F (50° C) Direct thermal
- Storage temperatures 4° F (-20° C) to 140° F (60° C)
- Operating humidity 35-75% non-condensing R.H.
- Storage humidity 10-90% non-condensing R.H.
- Electrical 24 VDC, ± 10%, average 6 A, peak 12 A
- Agency approvals UL cUL CE

Physical Characteristics

- Width 11.3" (286 mm)
- Height 3.07" (78 mm)
- Depth 6.73" (171 mm)
- Weight 10.58 lbs (4.8 kg)

Related Products

Options

- Paper near end sensor
- weekend paper low sensor
- RS-232 Serial interface
- Communication and Interface Capabilities
- Parallel IEEE-1284 and USB
- Optional external RS-232 Serial
- Windows and Linux drivers. Direct addressing with ESC sequences.
- Bar Codes/Symbologies
- Linear

销售热线

021-51088173
021-51088351

热销产品



Code 39
Fonts and Graphics
Up to eight bitmap fonts

[条码新闻](#) | [网站地图](#) | [友情链接](#) | [人才招聘](#) | [法律条款](#) | [在线解答](#) | [联系我们](#)

版权所有 © 2005 - 2011 上海竞阳科技

电话: 021-51088351 51088173 传真: 021-58527920

地址: 上海市浦东大道1097号15号楼3层D座 邮编: 200135 邮箱: mail@gyoung.com.cn