



全国统一服务热线: 400-1166-021

首页 | 关于公司 | 条码产品 | 自主开发 | 应用方案 | 下载中心 | 条码知识 | 条码新闻 | 在线留言 | 联系我们

- 条码打印机
- 条码扫描器
- 数据采集器
- 条形码软件



- 条码打印机
- 条码扫描器
 - 美国Intermec条码扫描器
 - 美国Symbol条码扫描器
 - 意大利Datalogic条码扫描器
 - HHP(honeywell)条码扫描器
 - 台湾Gyoung条码扫描器
 - 台湾CipherLAB条码扫描器
 - 福建新大陆条码扫描器
 - 日本Opticon条码扫描器
 - 日本DENSO条码扫描器
 - 美国Metrologic条码扫描器
 - 美国PSC条码扫描器
 - 美国Microscan扫描平台

- 数据采集器
- 无线局域网
- 条码标签
- 条码碳带
- 条码软件
- 条码检测仪
- 条码打印机配件
- Rfid电子标签

条码扫描器 > 意大利datalogic条码扫描器 > Datalogic QuickScan QS2500条码扫描器



Datalogic QuickScan QS2500手持式条码扫描器

DATALOGIC QuickScan QS2500手持式条码扫描器性能强。QuickScan 2500 工商用手持近距虹光条形码阅读器，突破科技极限、符合人体工程学的外观设计，是您在生产物流、仓储管理上不可或缺的最佳助手。内置解码器，准确识读各种一维条码。

技术参数

Operational	
Mechanical	
Length	4.5" / 11.5 cm
Width	2.9" / 7.4 cm
Height	7.3" / 18.5 cm
Weight	6.3 oz. / 179 g (cable not included)
Optical	
Light source	660 nm Visible Red Diode
Scan rate	200 scans/sec.
Scan width	4.0" / 10.2 cm at 5.0" / 12.7 cm from the label
Depth-of-Field	Label Density Range
Printing resolution, contrast and ambient light dependent	5 mils 1.8" to 4.5" - 4.4 to 11.4 cm
	13 mils 0.5" to 6.0" - 1.3 to 15.2 cm
	20 mils 1.0" to 8.5" - 2.5 to 21.6 cm
Resolution	5 mils / 0.13mm
Print contrast ratio	35% or higher
Pitch	±60°
Skew	±75°
Scan angle	46°
Ambient light immunity	Artificial & sunlight: 6,968 foot-candles / 75,000 Lux
Electrical	
Operating voltage	+5 VDC ±5%
Operating current	Operating: 225 mA @ 5 VDC , Standby: 100 mA @ 5 VDC
Environmental	
Temperature	Operating: 32° to 113° F / 0° to 45° C Storage: -22° to 149° F / -30° to 65° C
Humidity	5 to 95% NC
Shock	Withstands ten 5.0' / 1.5 m drops onto concrete
Physical shock	1500 g, 1 ms
Water & Dust	Resistant, IEC 60529 rating IP42DW
ESD protection	Functional after 15kV discharge
Communications	
Single interface	Keyboard Wedge
Humidity	5% to 95% relative humidity, non-condensing
Light Levels	Up to 4842 Lux (450 footcandles)
Contaminants	Sealed to resist airborne particulate contaminants
Ventilation	None required
Decoding Capability	
	UPC A, E / EAN 8, 13 / JAN 8, 13 (including add-ons P2 / P5, Code

销售热线

021-51088173
021-51088351

热销产品



Autodiscriminates	128), Code 128, Codabar, Pharmacode 39, Code 93, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code 39, Code 11, Code 16K, UK/Plessey, MSI/Plessey, Telepen, RSS 14, RSS-14 Stacked, RSS-14 Expanded, RSS Limited, PDF417 w/audio assist
Safety & Regulatory	
Electrical- Complies to	UL, cUL, EN60950
Emissions - Complies to	FCC, EN 55022, BSMI CNS 13438, AS/NZS 3548, VCCI

[条码新闻](#) | [网站地图](#) | [友情链接](#) | [人才招聘](#) | [法律条款](#) | [在线解答](#) | [联系我们](#)

版权所有 © 2005-2011 上海竞阳科技

电话: 021-51088351 51088173 传真: 021-58527920

地址: 上海市浦东大道1097号15号楼3层D座 邮编: 200135 邮箱: mail@gyoung.com.cn 