



全国统一服务热线: 400-1166-021

首页 | 关于公司 | 条码产品 | 自主开发 | 应用方案 | 下载中心 | 条码知识 | 条码新闻 | 在线留言 | 联系我们

- 条码打印机
- 条码扫描器
- 数据采集器
- 条形码软件



竞阳科技



条码打印机

条码扫描器

- 美国Intermec条码扫描器
- 美国Symbol条码扫描器
- 意大利Datalogic条码扫描器
- HHP (honeywell) 条码扫描器
- 台湾Gyoung条码扫描器
- 台湾CipherLAB条码扫描器
- 福建新大陆条码扫描器
- 日本Opticon条码扫描器
- 日本DENSO条码扫描器
- 美国Metrologic条码扫描器
- 美国PSC条码扫描器
- 美国Microscan扫描平台

数据采集器

无线局域网

条码标签

条码碳带

条码软件

条码检测仪

条码打印机配件

Rfid电子标签

二维条码扫描器 > 美国symbol二维条形码扫描器 > Symbol DS3478二维无线条码扫描器



Symbol DS3478二维无线条码扫描仪

Dimensions: 7.34 in. L x 4.82 in. W x 2.93 in. D (18.65 cm H x 12.25 cm W x 7.43 cm D)
 Weight (without cable): 14.6 oz. (414 gm)
 Battery 2200 mAh Lithium Ion Battery
 Battery charge time Fully charged (100%) in 3 hours
 Color: Twilight Black/Yellow
Performance Characteristics
 Light Source: 650 nm visible laser diode
 Resolution 640 x 480
 Minimum Element Width: 5 mil (0.127 mm)
 Nominal Working Distance: See Decode Zone
 Print Contrast: 25% minimum reflective difference
 Roll (Tilt): +/- 50 degrees from normal
 Pitch: +/- 60 degrees from normal
 Skew (Yaw): +/- 180 degrees from normal
 1D Codes UPC.EAN, UPC.EAN with Supplementals, UCC.EAN 128, JAN 8 & 13, Code 39, Code 39 Full ASCII, Code 39 Trioptic, Code 128, Code 128 Full ASCII, Codabar (NW7), Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, Code 32, Bookland EAN, IATA, UCC/EAN RSS and RSS variants
 2D codes PDF417, microPDF417, Maxicode, Data Matrix (ECC 2000), Composite Codes, QR Code
 Postal codes U.S. Postnet, U.S. Planet, U.K. Postal, Japan Postal, Australian Postal, Dutch Postal
 Interfaces supported RS232, Keyboard Wedge, Wand Emulation, Scanner Emulation, IBM 468X/469X, USB and Synapse
User Environment
 Operating Temperature: 32? to 122?F (-0? to 50?C)
 Storage Temperature: -40? to 140?F (-40? to 60?C)
 Humidity: 5% to 95% relative humidity, noncondensing
 Sealing: Sealed to IP65 specifications
 Drop Specifications: Unit functions normally after repeated 6.5-ft. (2-m) drops to concrete
 Ambient Light Immunity: Immune to direct exposure of normal office and factory lighting conditions, as well as direct exposure to sunlight:
 Outdoor: 10,000 foot-candles/107,600 Lux
 Electrostatic Discharge: Conforms to 15 kV air discharge and 8 kV of contact discharge
Radio specification
 Radio range 100 meters direct line of sight.
 Frequency 2.4 GHz
Regulatory
 Input Transient Protection: IEC 1000-4-(2,3,4,5,6,11)
 EMI/RFI: FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive, Japan VCCI/MITI/ Dentori
 Laser Safety: CDRH Class II, IEC Class 2

销售热线

021-51088173
021-51088351

热销产品



条码新闻 | 网站地图 | 友情链接 | 人才招聘 | 法律条款 | 在线解答 | 联系我们

版权所有 © 2005-2011 上海竞阳科技

电话: 021-51088351 51088173 传真: 021-58527920

地址: 上海市浦东大道1097号15号楼3层D座 邮编: 200135 邮箱: mail@gyoung.com.cn